

MERICRUSHER

MJHS-311 DTX

For versatile crushing



MERICRUSHER

MERICRUSHER

MJHS-311 DTX

For versatile crushing

MERICRUSHER WORKING ENVIRONMENTS

FOREST

- Crushing of harvesting leftovers
- Preparing of hauling lines
- Soil preparing for planting
- Maintenance of forest roads
- Clearing of vegetation and undergrowth

AGRICULTURE

- Clearing of new farm land (forest to farm clearing)
- Reclaiming soil for farming
- Orchard clearing
- Farm road maintenance

EQUIPMENT

FEATURES

- Bolt mounted counter blades
- Hardox liner (frame) bolt mounted
- UNT or UNTH Rotor with cost effective carbide cutters
- POC - Pressure operated safety clutch (SUOKONE patented)
- Possibility to turn the direction of the rotor
- Bolt mounted lift arm brackets

CONSTRUCTION

- Clearing of building sites
- Crushing of stumps
- Clearing of power lines
- Right of way clearing
- Clearing of firebreaks

OPTIONS

- Slip alarm (12V)
- Sizing screen rotating (hydraulic front/rear)
- Sizing screen door type (hydraulic front/rear)
- Rear roller (hydraulic)
- Guide plate (hydraulic front/rear)
- Hydraulic Top Link
- Multiple cutter options available

Base machine demand

Tractor

Mounting

CAT 3

Auxiliary hydraulic

3 pcs. double acting

PTO

1000 rpm

Working speed

Creeper gear recommended

Technical data:

Power range

400 - 700 hv

Transmission

Mechanical PTO

Final transmission

Gear (X-serie)

Clutch

POC-3 XL

Rotor diameter / width

600 / 3110mm

24 / 122 inch

Cutter qty.

130 (UNTH Rotor)

Working depth

300 mm / 12 inch

Main dimensions:

Length

2540 mm

100 inch

Width

3610 mm

142 inch

Height

1430 mm

57 inch

Weight

3250 kg

7200 lbs

Weight, with options

4630 kg

10200 lbs



SUOKONE OY
88610 Vuokatti
FINLAND

tel. +358 86 66 2011
suokone@suokone.com
www.mericrusher.com